

NATIONAL INSTITUTE OF PHARMACEUTICAL EDUCATION AND RESEARCH (NIPER - KOLKATA)

4, RAJA S. C. MULLICK ROAD, JADAVPUR, KOLKATA - 700 032

No. E-12/11/1/17/NK/Works-2/2017 30th August, 2017

Notice Inviting Quotation(s)

A sealed quotation is hereby invited from amongst the interested parties having valid license, credentiality and other relevant documents for installation of Greenlam sturdo vibrance serene toilet cubicle and privy divider panels for urinal at certain places for partition of the toilets at "Chunilal Bhawan", 168, Manicktala Main Road, Kolkata – 700 054. The specification and requirement of items may be downloaded from the attached file. The interested parties/bidders may submit their quotation(s) duly filled in and signed, so to reach the Director, NIPER-Kolkata latest by 18th September, 2017 upto 03:00 P.M. and the same will be opened on the same day at 03:30 P.M. at NIPER-Kolkata office.

Enclo: Specification

S/d

Director, NIPER-Kolkata

Specification for Greenlam sturdo vibrance Serene Toilet Cubicle and Privy Divider Panels:

SI. No.	DESCRIPTION OF WORK	QTY	RATE PER UNIT	AMOUNT (inclusive of Tax)
01.	Providing & fixing Greenlamsturdovibrance Serene Toilet Cubicle (of following standard dimension which includes 600mm door size width) made of heat, bacteria, water, chemical, scratch impact and anti-bacterial resistant 12mm thick sold compact laminated panels tested by shriram Test House Finish of the compact laminated should be Suede/*Raw silk, which includes the door, pilasters & intermediate panelsfinished with approved texture/shade as per the detail drawings & as per (IS2046(Indian standard) and as per fire retardant B5-47697 standard. The product should have Green Guard Certificate.			
	This also includes providing and fixing in position necessary hardware made out Nylon Polyamid Gread-6 & Aluminum powder coated top rail as per manufacture's specification like Door Knob, Gravity Hinges Aluminum top rail, coat hooks, U Channels, Adjustable foot, Noise Deafening Tape, screws and wall plugs etc.			
	The top fitting should consist of aluminium powder coated top rail which will get fixed with Mid and Pilasters.			
	All screw will of 304 gread in SS with stain finish. Top rail is extruded Aluminium will be powder coated or anodized. All pilaster is supported by grade 6 Nylon Polyamide Thermoplastic plam design pedestal with non-corrosive steel inserts. The base diameter 65mm and neck diameter of 33mm anchored to the floor with SS screw with push fit capping at a clearance height of 150mm. Model is heat and Bacteria Resistant Polyamide in which aluminium U channel will be used for the fixing of intermediate panels to the wall.			
	Toilet Cubical with dimension1200mm X 1200mm X 1995mm (Height), which includes 600mm door size width.			
	Gr.Floor 2 (L) + 1 (G) = 3 Unit 1 st Floor 1 (G) + 1 (G) = 2 Unit 2 nd Floor 2 (L) + 1 (G) = 3 Unit Total = 08 Unit	08 Units		
02.	Providing & fixing vibrant coloured Privy Divider Panel laminates coupled for urinal partitionwith rust resistant stainless steel fittings. Composed with superior product features to provide greater privacy and hygiene to the users. The urinal partitions are manufactured using 12mm thick Compact Laminates, in accordance to IS-0002046-199/BSEN-438(1)-91.Gap from floor 500mm-600mm			
	Size: 1200mm (Height) X 450mm	08		